



Label Printer (LP100)

The OCS Label Printer (LP100) ensures the highest quality standards with regard to the labelling of, and repair of defects on, polymer films. Simple operation enables reliable and fast printing.

Labelable Materials

- Polymer films (tape)

Features

- Reliable and fast printing
- Precise impression
- Easy operation
- Compact design
- Meets the highest quality standards

Compatible with

- OCS Tape Line
- OCS Modular Film Analyser (MFA)

Sales Team



T +49 2302 95622-0
F +49 2302 95622-33
info@ocsgmbh.com
www.ocsgmbh.com

Address

OCS Optical Control Systems GmbH
Wullener Feld 24
58454 Witten
Germany

More Product Pictures





Similar Products




LASER Marking System (LM100)

The OCS LASER Marking System is designed and manufactured using state-of-the-art technology. The LM100 can be used to mark or label defects on polymer films (tape). The labelling and marking settings as well as the power of the laser can be configured with the operator software to the corresponding product requirements. The LASER Marking System consists of laser, control and suction unit. The laser unit essentially consists of a class 4 air-cooled laser, a two-part protective cover, a viewing window and a pneumatically swivelling film guide. The laser unit has two air filters so that neither dirt nor dust ... [read more on our Website]




Modular Film Analyser (MFA)

The OCS Modular Film Analyser (MFA) is used for the continuous cooling, stripping and winding of extruded polymer film. In combination with a variety of different measuring instruments, a wide range of applications for the analysis of different sample materials is covered. In addition to the Film Surface Analyser (FSA100V2/FSA200V2) for optical quality control of the polymer film, online spectroscopy, the measurement of haze and transmission as well as gloss and thickness can be integrated. This allows the combination of a tailor-made and yet economical solution. [vc_column width="1/2"] Features Modular architecture for customer-specific configuration with different measurement devices Homogeneous, ... [read more on our Website]



Tape Line (SSA®)

The OCS Tape Line type SSA® is used specifically to detect surface irregularities (pips) on non-transparent polymer films (tape) in the wire and cable industry. The SSA® Line consists of a Measuring Extruder (ME) and a Modular Film Analyser with a Chill Roll (MFA-CR). During the measurement of the surfaces, the extruded polymer film (tape) passes over a chill roll, which leads the tape to the Surface Quality Analyser (SQA). This high-resolution CMOS camera system uses a specially developed measuring roll to measure the height of the surface defects (so-called pips or agglomerates) with a resolution of 1 ... [read more on our Website]



Tape Line (TCA®)

The OCS Tape Line Type TCA® is used for testing transparent polymer films (tape). It consists of the OCS Measuring Extruder (ME) and the OCS Modular Film Analyser with Calender (MFA-Calender). Our calendaring system has been specially developed for the wire and cable industry. It presses and cools the extruded polymer film (tape) from both sides, thus ensuring a smooth and consistent surface thickness for optical analysis. The Tape Quality Analyser (TQA100) contains a high-resolution camera system that detects contaminants, gels, black specks, fibres and metal particles. The detected errors are marked by the LASER Marking System (LM100) or ... [read more on our Website]

Images, drawings and data are non-binding and subject to modification without prior notice. © 2026. All rights reserved - OCS Optical Control Systems GmbH | Wullener Feld 24 | 58454 Witten, Germany